

PICO⁺ pH/Conductivity Meter



pH Meter

This bench-top pH meter is an ideal help in every laboratory for routine or R&D level measurement. This very handy instrument measures pH, mV and has 40 - point data memory storage.

Instrument has two operating modes - (a) Standard mode (b) GLP mode : 40 data readings can be stored, printed and scanned on display. For GLP mode, additional entries of sample name and ID number can be stored. The optional Data logging function enables user to store 24 data points consisting of pH, temperature and time readings. For example as required in kinetic study or in any chemical reaction. Time intervals from 1min. to 1Hr. in steps of 1min. are available. User entries of pH limit values make the data more defined and informative.

Conductivity Meter

LABINDIA offers the perfect choice of a bench -top conductivity meter for measurements in the laboratories - whether routine or at R & D level. The conductivity meter offers better operating comfort and measuring confidence in all areas of application. Due to user selective temperature function, instrument calculates the conductivity at the reference temperature 25 +/- 0.1°C with linear function. Conductivity is an important factor in water analysis for quality of drinking water, direct ionic concentration measurement in pharmaceutical preparations, waste water treatment plants, pollution control in lakes & rivers, boiler feed water and oceanography to determine salinity and TDS.

Common Features

- Advanced microcontroller based user friendly state-of-the-art design.
- PICO pH Meter complies to USP and DIN standards.
- Sleek moulded cabinet with alphanumeric splash waterproof polyester keyboard with soft keys.
- User interactive software in dialogue mode for ease of operation with protection against invalid entries.
- 20 x 2 line back lighted LCD display.
- Simultaneous measurement of pH, mV and temperature. Conductivity, TDS & Salinity optional.
- Non-volatile memory storage of :
 - a) 40 pH and 40 mV readings with temperature in pre-selected GLP or Non-GLP format.
 - b) 24 data memory readings of pH, temperature and time in data logging mode (optional).
- Password protection for calibration data and stored Readings.
- Calibration data with date and time stamp for authentication. Facility to view the calibration data.
- Calibration reminder alarm.
- Alphanumeric entries of sample name, identification number for authentication.
- Input stability indicator for reproducible results.
- Built-in real time clock (RTC) for time display and on report printout.
- Factory entered CUSTOMER NAME on report printout for authentication.
- Error indication helps the user to trace the problem.
- Audible beep indication during valid key operation.
- PC compatibility for data downloading (optional)
- Combined pH and conductivity instrument is available.

pH Meter

- Automatic temperature compensation by Pt.100 temperature sensor. Range 0° to 150°C.
- 3 point (Isopotential) or 5 point (linear or segmented) calibration protocol.

Conductivity Meter

- Automatic evaluation of CELL constant with standard solution.
- User selectable temperature coefficient for automatic temperature compensation, through special TEMPCO key.
- Input stability indicator for reproducible results.

Specifications

Common Specifications

Temperature	
Temperature range	0 to 150°C
Resolution	0.1°C
Relative accuracy	+/- 0.2°C
Sensor	RTD Pt100
Temp. Compensation	Automatic / Manual
Display	20 x 2 line back-lit LCD Display
Keyboard	Alphanumeric splash water-proof polyester soft keys.

Output

a) Printer	Parallel Port
b) RS 232C	PC connectivity

Environmental Operating Conditions

a) Operation	Indoor
b) Temperature	Ambient to 45° C
c) Relative humidity	5 to 90% non-condensing

Power Requirement 230 Vac, +_10% / 50Hz., 10 W

Dimensions 305 x 220 x 70mm (W x D x H)

Weight 2.2 kgs

pH Meter Specifications

pH range	-2.00 to 19.999
Resolution	0.1/ 0.01/ 0.001 pH
Relative Accuracy	+/- 0.002 pH
Slope	3 points 80% to 120%, 5 points 90% to 105%
Sensor	Combination pH electrode
Calibration	Auto-calibration & printout of calibration Report.

millivolt

mV range	0 to +/- 1999.9 mV
Resolution	+/- 0.1 mV
Relative accuracy	+/- 0.2 mV

Input

1 BNC, 1 Banana, 1 ATC - PT 100

Input Impedance

> 10¹²ohms

Report format

- (a) Report of selected pH & mV reading with temperature.
- (b) Calibration report
- (c) Data table & Graph (optional)

Conductivity Meter Specifications

Conductivity Measuring Range Autoranging 0.01µS/cm to 199.9 mS/cm. (Depending on the cell used 0.1/1.0/10.K)

Resolution 0.01 (displayed)

Accuracy 0.5%

Input

2 - Banana socket for conductivity electrode, 1-ATC-PT100

Report format

- (a) Calibration report
- (b) Report of all selected Conductivity, TDS & Salinity readings

LABINDIA
ANALYTICAL
WHERE COMMITMENT IS CULTURE

www.labindia-analytical.com / For Enquiries: sales.mfd@labindia.com

Labindia Analytical Instruments Pvt. Ltd.

HEAD OFFICE:

Thane: 201, Nand Chambers, LBS Marg, Near Vandana Cinema, Thane (W) - 400 602.
Tel.: +91-22-2598 6000 / 2598 6110 Fax: +91-22-2541 0420 / 2533 5940 E-mail: sales.mfd@labindia.com

REGIONAL OFFICES:

Delhi: Tel.: +91-11-4330 6001 / 10 Chennai: Tel.: +91-44-2434 7008 / 2432 0352 Kolkatta: Tel.: +91-33-2466 1396 / 2466 3362

BRANCH OFFICES:

Bangalore: Tel.: +91-80-2323 0919 / 20 / 21 Lucknow: Tel.: +91-522-2346 535 / 2346 496 Hyderabad: Tel.: +91-40-4444 3456
Tiruvanthapuram: Tel.: +91-471-2324 064 / 2320 082 Vadodara: Tel.: +91-265-2986 005 / 2986 006 Pune: Tel.: +91-20-2545 3386
Chandigarh: Tel.: +91-172-4090 001-07 / 4090 009

FACTORY: Plot No. EL-72, Electronic Zone, TTC Industrial Area, Thane Belapur Road, Navi Mumbai - 400 705.

Tel.: +91-22-2762 6660 / 61 / 62 / 63 / 6516 3480 / 81 / 6107 6666 Fax: +91-22-27626664 E-mail: lipfactory@vsnl.net

APPLICATION & TRAINING CENTRE: R-909, TTC Industrial Area, Thane Belapur Road, Rabale, Navi Mumbai - 400 701.

Tel.: +91-22-2760 6955 / 6107 6555 Fax: +91-22-2760 6706



Striving to become the best individuals, we endeavour to foster the best team. Performing sensibly, we try to achieve the best efficiency. Working innovatively, we seek to make the best products. Listening patiently, we excel to offer the best service. So, no matter what you needs are, come to us, GET THE BEST

LABINDIA reserve the right to change specification without notice as part of its continuous programme of product development.